

# STEEL SPECIFICATIONS

	CARRIAGE HOUSE DESIGN								TRADITIONAL DESIGN							
	CLASSICA 1000	CLASSICA 2000	CLASSICA 3000	OAK SUMMIT 1000	OAK SUMMIT 2000	OAK SUMMIT 3000	FIMBEL DC-400	FIMBEL DC-500	HERITAGE 1000	HERITAGE 2000	HERITAGE 3000*	STRATFORD 1000	STRATFORD 2000	STRATFORD 3000**	FIMBEL OLYMPUS 400	FIMBEL OLYMPUS 500
<b>PANEL DESIGNS</b>	✓	✓	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓		
Short									•	•	•	•	•	•	•	•
Long									•	•	•	•	•	•	•	•
Flush									•	•	•			•		
Ribbed											•			•		
Carriage House	8 Designs	8 Designs	8 Designs	3 Designs	3 Designs	3 Designs	1 Design	1 Design								
<b>CONSTRUCTION LAYERS</b>																
Steel	•			•					•			•				
Steel + Insulation		•			•					•			•			
Steel + Insulation + Steel			•			•	•	•			•			•	•	•
<b>DOOR THICKNESS</b>																
1 3/8" (3.5cm)						•	•							•	•	•
2" (5.1cm)	•	•	•	•	•			•	•	•	•	•	•			•
<b>INSULATION</b>		Polystyrene <sup>1</sup>	Polyurethane <sup>1</sup>		Polystyrene <sup>1</sup>	Polystyrene <sup>1</sup>	Polyurethane	Polyurethane		Polystyrene <sup>1</sup>	Polystyrene <sup>1</sup>		Polystyrene <sup>1</sup>	Polystyrene <sup>1</sup>	Polyurethane	Polyurethane
R-VALUE		6.84	13.35		6.84	6.58	11.04	15.67		6.84	9.19		6.84	6.58	11.04	15.67
<b>STEEL THICKNESS</b>																
Gauge (ga)	24 ga	24 ga	25/27 ga	25 ga	25 ga	27/27 ga	25/27 ga	25/27 ga	24 ga	24 ga	24/27 ga	25 ga	25 ga	27/27 ga	25/27 ga	25/27 ga
Gauge (mm)	0.61mm	0.61mm	0.53/0.42	0.53mm	0.53mm	0.42/0.42mm	0.53/0.42	0.53/0.42	0.61mm	0.61mm	0.61/0.42	0.53mm	0.53mm	0.42/0.42	0.53/0.42	0.53/0.42
<b>WOODGRAIN EXTERIOR TEXTURE</b>	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
<b>END STILES</b>																
Galvanized	•	•		•	•							•	•			
Painted			•			•	•	•	•	•	•			•	•	•
<b>THERMAL SEAL</b>																
BOTTOM WEATHER SEAL	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Steel Retainer	•	•	•	•	•				•	•		•	•			
Aluminum Retainer						•					•			•		
Duo-Durometer Astragal							•	•							•	•
<b>DECORATIVE WINDOW OPTIONS</b>	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
<b>WINDOW GLASS OPTIONS</b>																
3/32" (0.24cm) Single Strength				•	•	•	•	•	•	•	•	•	•	•	•	•
1/8" (0.32cm) Tempered Dbl Strength	•	•	•													
Insulated Glass			•			•	•	•			•			•	•	•
Obscure (not shown)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
<b>DECORATIVE HARDWARE OPTIONS</b>	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
<b>EXTERIOR COLOR OPTIONS</b>																
True White	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Almond				•	•	•	•	•	•	•	•	•	•	•	•	•
Sandtone	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Brown							•	•	•	•	•			•	•	•
Hunter Green														•		
Gray														•		
Woodgrain	•	•	•			•								•		
<b>WIND LOAD<sup>2</sup> AVAILABLE</b>	•	•	•	•	•	•			•	•	•	•	•	•		
<b>WARRANTY</b>																
Paint Finish <sup>3</sup>	Lifetime	Lifetime	Lifetime	15 Years	25 Years	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	15 Years	25 Years	Lifetime	Lifetime
Workmanship/Hardware <sup>3</sup>	3 Years	5 Years	Lifetime	1 Year	2 Years	3 Years	5 Years	Lifetime	3 Years	5 Years	Lifetime	1 Year	2 Years	3 Years	5 Years	Lifetime

✓ Amarr's section interfaces are designed to reduce the risk of serious finger and hand injuries.

\* Formerly WeatherGuard™ Plus  
\*\* Formerly WeatherGuard™

<sup>1</sup> All Insulation on Amarr brand doors has passed fire safety testing.

<sup>2</sup> It is your responsibility to make sure your garage door meets local building codes.

<sup>3</sup> For complete warranty details, visit [amarr.com](http://amarr.com) or contact your local Amarr dealer.

NOTE: Optional door locks and various heights and widths are available thru your local garage door dealer.